



# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 31/05/2013

Revision date: 31/05/2013

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : One Step Universal Bond  
Product code : S-Chem-508  
Product group : Commercial product  
Other means of identification : L/C Quick-Cure HZ Bonding Resin

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/preparation : For Professional Dental Use  
Adhesion restorative primer  
Function or use category : Adhesives, binding agents

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Septodont, Inc.  
416 S. Taylor Ave.  
Louisville, CO 80027

T 303-665-7535

[www.septodontusa.com/home](http://www.septodontusa.com/home)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC  
001-703-524-3887

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008

##### GHS/CLP classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Eye Irrit. 2B H320  
Skin Sens. 1 H317  
STOT SE 3 H336

#### Adverse physicochemical, human health and environmental effects

No additional information available

# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 2.2. Label elements

#### GHS-US labelling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapour  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H320 - Causes eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US)

: P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing fume, mist, spray, vapours  
P264 - Wash hands and forearms thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P272 - Contaminated work clothing should not be allowed out of the workplace  
P280 - Wear eye protection, protective gloves  
P302+P352 - IF ON SKIN: Wash with plenty of water  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CENTER/doctor if you feel unwell  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use water, carbon dioxide (CO<sub>2</sub>), powder and foam for extinction  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container according to local, regional, national, and international regulations

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Acetone	(CAS No.) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8	45 - 55	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-Hydroxyethyl methacrylate	(CAS No.) 868-77-9 (EC no) 212-782-2 (EC index no) 607-124-00-X	5 - 15	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
2-Propenoic acid, 2-methyl-, 2-hydroxy-1,3-propanediyl ester	(CAS No.) 1830-78-0 (EC no) 217-388-4	1 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of R-, H- and EUH-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : If medical advice is needed, have product container or label at hand.
- First-aid measures after inhalation : If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.
- First-aid measures after skin contact : Immediately rinse with plenty of water. Remove contaminated clothing. Wash contaminated clothing before reuse. Obtain medical attention if irritation persists.
- First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open. If eye irritation persists: Get medical advice and attention.
- First-aid measures after ingestion : If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Irritation to eyes, skin and respiratory tract.
- Symptoms/injuries after inhalation : Difficulty in breathing. Cough. Dry/sore throat.
- Symptoms/injuries after skin contact : Causes skin irritation. Repeated or prolonged skin contact may cause dermatitis and defatting.
- Symptoms/injuries after eye contact : Causes eye irritation.
- Symptoms/injuries after ingestion : Abdominal pain. Nausea.
- Chronic symptoms : May cause an allergic skin reaction.

### 4.3. Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container or label at hand.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Foam, powder, carbon dioxide (CO<sub>2</sub>), water spray.
- Unsuitable extinguishing media : Use of heavy stream of water may spread fire.



# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition : Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.
- Explosion hazard : Product is not explosive.
- Reactivity : Stable at ambient temperature and under normal conditions of use.

### 5.3. Advice for firefighters

- Firefighting instructions : Do not breathe fumes from fires or vapours from decomposition. All fire-fighting personnel must wear safety suits.
- Protection during firefighting : Use normal individual fire protective equipment. Use self-contained breathing apparatus when fighting fire in an enclosed area.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Do not get in eyes, on skin, or on clothing.

#### 6.1.1. For non-emergency personnel

- Protective equipment : During cleaning/processing wear suitable respiratory equipment. Wear suitable protective clothing, gloves and eye/face protection.
- Emergency procedures : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Ventilate area. Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing, gloves and eye/face protection. Use recommended respiratory protection.
- Emergency procedures : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Ventilate area. Evacuate unnecessary personnel.

### 6.2. Environmental precautions

Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

### 6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material, then place in suitable container.
- Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Avoid contact with skin and eyes.
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Always wash hands after handling the product. Do not eat, drink or smoke when using this product. Ensure there is adequate ventilation. Wear recommended personal protective equipment.

# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Do not eat, drink or smoke in areas where product is used.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in original container. Store in a dry, cool place. Store in a well-ventilated place. Keep container tightly closed.

Storage area : Store away from heat.

Special rules on packaging : Keep container closed when not in use.

### 7.3. Specific end use(s)

Adhesion restorative primer

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

2-Hydroxyethyl methacrylate (868-77-9)		
Lithuania	IPRV	20 mg/m <sup>3</sup>
Norway	Gjennomsnittsverdier (AN)	11 mg/m <sup>3</sup> ; 2 ppm
Norway	Gjennomsnittsverdier (Korttidsverdi)	16.5 mg/m <sup>3</sup> ; 4 ppm

Acetone (67-64-1)		
EU	IOELV TWA	1210 mg/m <sup>3</sup> ; 500 ppm
France	VLE	2420 mg/m <sup>3</sup> ; 1000 ppm (restrictive limit)
France	VME	1210 mg/m <sup>3</sup> ; 500 ppm (restrictive limit)

### 8.2. Exposure controls

Appropriate engineering controls : Ensure adequate ventilation, especially in confined areas.

Personal protective equipment : Protective goggles. Gloves.  
Insufficient ventilation: wear respiratory protection.



Materials for protective clothing : Butyl-rubber protective gloves.

Hand protection : Impermeable protective gloves.

Eye protection : Safety glasses.

Skin and body protection : Handle in accordance with good industrial hygiene and safety practice. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Wear suitable protective clothing. Wash contaminated clothing before reuse. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls : Ensure adequate ventilation, especially in confined areas.

Consumer exposure controls : Wear recommended personal protective equipment.

# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colorless
Odour	: Sweet; Pungent
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 56.1 °C (133 °F) (Acetone)
Flash point	: -18 °C (-0.4 °F) (Acetone)
Self ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: 2 (Air = 1) (Acetone)
Relative density	: No data available
Density	: > 1 g/cc
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable at ambient temperature and under normal conditions of use.

#### 10.2. Chemical stability

Stable at standard temperature and pressure.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

No additional information available

#### 10.5. Incompatible materials

No additional information available



# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 10.6. Hazardous decomposition products

Under conditions of fire this material may produce: Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>2-Hydroxyethyl methacrylate (868-77-9)</b>	
LD50 oral rat	5050 mg/kg
LD50 dermal rabbit	> 3000 mg/kg

<b>Acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg

Irritation : Irritating to eyes and skin.  
Corrosivity : Not classified  
Sensitisation : May cause sensitisation by skin contact.  
Repeated dose toxicity : Not classified  
Carcinogenicity : Not classified  
Mutagenicity : Not classified  
Toxicity for reproduction : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>2-Hydroxyethyl methacrylate (868-77-9)</b>	
LC50 fish 1	213 - 242 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	227 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

<b>Acetone (67-64-1)</b>	
LC50 fish 1	4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>2-Hydroxyethyl methacrylate (868-77-9)</b>	
BCF fish 1	1.34 - 1.54
Log Pow	0.47

<b>Acetone (67-64-1)</b>	
BCF fish 1	0.69
Log Pow	-0.24

### 12.4. Mobility in soil

No additional information available

# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Do not dispose of waste into sewer.  
Waste disposal recommendations : Dispose of waste material in accordance with all local, regional, national, and international regulations.

## SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

### 14.1. UN number

UN-No. : UN1993

### 14.2. UN proper shipping name

Proper Shipping Name : FLAMMABLE LIQUID, N.O.S.  
Transport document description : UN 1993 FLAMMABLE LIQUID, N.O.S. (Contains: Acetone), 3, II, (D/E)

### 14.3. Transport hazard class(es)

Class (UN) : 3  
Hazard labels (UN) : 3



### 14.4. Packing group

Packing group (UN) : II

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Authorisations and/or restrictions on use (Annex XVII):

3. Liquid substances or mixtures, which are regarded as dangerous according to the definitions in Council Directive 67/548/EEC and Directive 1999/45/EC.	One Step Universal Bond - 2-Hydroxyethyl methacrylate - Acetone - 2-Propenoic acid, 2-methyl-, 2-hydroxy-1,3-propanediyl ester
40. Substances meeting the criteria of flammability in Directive 67/548/EEC and classified as flammable, highly flammable or extremely flammable regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	Acetone

Contains no REACH candidate substance



# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 15.1.2. National regulations

#### Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### 2-Hydroxyethyl methacrylate (868-77-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### 2-Propenoic acid, 2-methyl-, 2-hydroxy-1,3-propanediyl ester (1830-78-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

### 16.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

F; R11

Xi; R36/38

Xi; R43

R67

R53


### Adverse physicochemical, human health and environmental effects

No additional information available

### 16.2. Label elements

Labelling according to Directive 67/548/EEC or 1999/45/EC

Hazard symbols



R-phrases

: R11 – Highly flammable  
R36/38 - Irritating to eyes and skin.  
R43 - May cause sensitisation by skin contact.  
R67 - Vapours may cause drowsiness and dizziness.  
R53 - May cause long-term adverse effects in the aquatic environment.

### 16.3. Other hazards

No additional information available

### 16.4 Additional Information

Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2

# One Step Universal Bond

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Flam. Liq. 2	Flammable liquids Category 2
Skin Irrit. 2	skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitisation Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
R11	Highly flammable.
R20/22	Harmful by inhalation and if swallowed.
R36	Irritating to eyes.
R36/37/38	Irritating to eyes, respiratory system and skin.
R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
F	Highly flammable
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*